

# Splitters 380-4000 MHz

**SKU:** 781001, 781002, 781003

## FEATURES

- Wide Frequency Band 380-4000 MHz
- Low VSWR
- Low Insertion Loss
- Indoor & Outdoor Application IP65
- Widely used for In-building Solutions
- 1-year warranty



## Specifications

### TECHNICAL

Model	781001	781002	781003
Frequency Band (MHz)	380-4000		
Number of Input	1		
Number of Output	2	3	4
Splitter Loss (dB)	3.0	4.8	6.0
Insertion Loss (dB)	≤0.7	≤1.2	≤1.2
Isolation	≥20	≥20	≥20
VSWR (average in band)	≤1.35		

### (cont'd)

Total Input Power (W)	50
Impedance (Ohm)	50
Connector	N-Female
Temp (deg)	-40°F - +80°F (-40°C - 176°C)
Application	Indoor or Outdoor, IP65

**† ⚠ WARNING:** This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer, and Bisphenol A, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## Package Dimensions

781001	3.75" L x 4.125" W x 1.0" H	I	.53 lbs.
781002	3.875" L x 6.25" W x 1.375" H	I	.82 lbs.
781003	4.625" L x 5.0" W x 1.0" H	I	.81 lbs.

## Support



**1 Year Warranty**

**US Web:** wilsonconnectivity.com      **INTL Phone:** +44 1223 982031  
**US Phone:** +1 800 871 1612

FOR PARTNER'S USE

## UPC

