

P-Lock

Locking Power Cables



STOP

ACCIDENTAL DISCONNECTS

P-Locks are available in Black, Blue and Red to easily identify main and redundant power sources at a glance. Color coding with P-Locks adds peace-of-mind and ensures maximum uptime.

Lock down your data center power cords with the P-Lock from LYNN. As more manufacturers are offering locking outlets, the P-Lock is quickly becoming the standard to prevent accidental disconnection of power cords from PDU outlets. P-Locks are designed with “P-shaped” clips on each side of the plug housing. These clips produce an audible “click” when inserted assuring a secure locking fit between the plug and the outlet.

FEATURES

- Male connector locks securely into locking PDU*
- UL Listed
- Ships coiled, never kinked
- Lifetime Warranty

SPECIFICATIONS

P-Lock C14 to C13

- Electrical Rating: 10 Amp, 250 Volt
- Temperature Rating: to 105° C
- Approvals: UL Listed, RoHS Compliant
- Jacket: SVT, 18 AWG

P-Lock C20 to C19

- Electrical Rating: 20 Amp, 250 Volt
- Temperature Rating: to 105° C
- Approvals: UL Listed, RoHS Compliant
- Jacket: SJT Jacket, 12 AWG

P-Lock C14 to C15

- Electrical Rating: 15 Amp, 250 Volt
- Temperature Rating: to 105° C
- Approvals: UL Listed, RoHS Compliant
- Jacket: SJT Jacket, 14 AWG



P-Lock

Locking Power Cables



Easy pinch design allows quick release from outlets

P-Lock is the only locking cable compatible with new high density Server Technology HDOT™ PDUs

P-tabs ensure that P-Lock cables lock securely into Raritan® SecureLock™* and ServerTech lockable PDUs



Feature

SUREFIT™ LOCKING SLEEVE

The SureFIT™ Locking Sleeve creates a strong connection and prevents power cables from being accidentally dislodged. Use SureFIT™ on the female end of your P-Lock Locking Power cable. Available for C13 and C19.

*all Raritan® iPDUs manufactured after June 2012 with part number prefix "PX2"

DID YOU KNOW?



While P-Lock Locking Cables will work in ANY PDU, they are 100% compatible with Raritan® SecureLock™ locking PDUs as well as ServerTech® Lockable PDUs. Tests have shown that P-Locks will lock into other major brands' locking PDUs as well.

*LYNN is not affiliated with Raritan® and SecureLock™ products or Server Technologies® and ServerTech™ products.

ORDERING INFORMATION

PWR - L - 2 - F

1 2 3 4 5 6 7 8 9

1 FEMALE SIDE
C13 = 3
C15 = 5
C19 = 9

2 MALE SIDE
C14 = F
C20 = T

3 JACKET TYPE
SJT = J
SVT = V

4 LABELS
Shipped w/
Label = L

5 AMPERAGE
10 AMP = 1
15 AMP = 5
20 AMP = 0

6 VOLTAGE
250v = 2

7 COLOR
Black = BK
Blue = BL
Green = GN
Red = RD

8 LENGTH
3-Digit Length
Examples:
001, 0.50, 01.5

9 UNIT OF MEASURE
Feet = F