



IPL350-3C SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL350-3C	3	3.52
IPL350-4C	4	4.57
IPL350-5C	5	5.62
IPL350-6C	6	6.67
IPL350-8C	8	8.77
IPL350-10C	10	10.87
IPL350-11C	11	11.92
IPL350-12C	12	12.97
IPL350-14C	14	15.07

WIRE ENTRY POINT  
WIRE RANGE: 350MCM - #10AWG  
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT.

		<b>POLARIS</b> SALES . CO . INC	
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE:  <b>INSULATED 350 CONNECTOR</b>	
NAME		DWG. NO.	
DRAWN BY T.MITCHELL		IPL350C SERIES	
REVISED		4/17/2024	
MATERIAL: N/A		SCALE: N/A	
SHEET: 1 OF 1			