

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

1 Identification of the substance and manufacturer

Trade name: NON-BLEED WHITE TRK MKR EXTRA
Other means of identification
Product code: 0000200782
Article category
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
 Eye irritation 2A H319 Causes serious eye irritation.
 Carcinogenicity 2 H351 Suspected of causing cancer.
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol. Pressurized container: may burst if heated.
 Causes serious eye irritation.
 Suspected of causing cancer.
 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-89-8	VM&P Naphtha	15-25%
1317-65-3	Calcium Carbonate	≥15-<20%
13463-67-7	titanium dioxide	10-15%
74-98-6	propane	10-15%
67-63-0	Isopropyl Alcohol	≥5-<10%
106-97-8	n-butane	5-10%
67-64-1	Acetone	1-5%
1330-20-7	xylene (mix)	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness

(Contd. on page 2)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: NON-BLEED WHITE TRK MKR EXTRA

(Contd. of page 1)

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****64742-89-8 VM&P Naphtha**

TLV (USA) Long-term value: 100 ppm
 Skin, A3

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 TLV (USA) see Appendix F Minimal oxygen content (D, EX)

67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm
 REL (USA) Short-term value: 1225 mg/m³, 500 ppm
 Long-term value: 980 mg/m³, 400 ppm
 TLV (USA) Short-term value: 984 mg/m³, 400 ppm
 Long-term value: 491 mg/m³, 200 ppm
 BEI, A4

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm
 TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm
 (EX)

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm
 REL (USA) Long-term value: 590 mg/m³, 250 ppm
 TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
 Long-term value: 594 mg/m³, 250 ppm
 A4, BEI

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm
 REL (USA) Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV (USA) Long-term value: 20 ppm
 BEI, A4

Ingredients with biological limit values:**67-63-0 Isopropyl Alcohol**

BEI (USA) 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

67-64-1 Acetone

BEI (USA) 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

(Contd. on page 3)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: NON-BLEED WHITE TRK MKR EXTRA

(Contd. of page 2)

1330-20-7 xylene (mix)

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

Hygienic protection: Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state	Aerosol
Odor:	Aromatic
Odor threshold:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flammability:	Extremely flammable.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	Not determined.
Solubility:	Not determined.
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Particle characteristics	Not applicable.
Appearance:	Aerosol.
Ignition temperature:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Water:	0.0 %
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****13463-67-7 titanium dioxide**

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

67-63-0 Isopropyl Alcohol

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

1330-20-7 xylene (mix)

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	6,350 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: No irritating effect.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: NON-BLEED WHITE TRK MKR EXTRA

Sensitization: No sensitizing effects known.

(Contd. of page 3)

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950
DOT UN1950
DOT Aerosols, flammable
ADR 1950 Aerosols
Transport hazard class(es):
Class 2.1 Gases
Special marking (IATA):
Packaging Group: --
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0	Isopropyl Alcohol
1330-20-7	xylene (mix)

Toxic Substances Control Act**(TSCA):** All ingredients are found on the inventory list of substances.**Canadian Domestic Substances List****(DSL):** All ingredients are listed or exempted.**Consumer Product Safety****Commission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

67-64-1	Acetone	I
1330-20-7	xylene (mix)	I

16 Other information**Contact:** Regulatory Affairs