

Flex Duct Support



Work. Perform. Outlast.
Limited Lifetime Warranty



Flexible duct is often susceptible to kinks and sags that restrict air flow. The FDS1 Flexible Duct Support eliminates air flow restrictions and increases efficiency to dramatically reduce utility bills and improve heated or air-conditioned room comfort. A properly supported 90° duct elbow typically improves air flow efficiency 10 to 40%. A Malco Duct Support quickly installs on new or existing flexible duct. The versatile FDS1 design uses either 36 or 48 inch nylon cable/zip ties to accommodate 4 inch to 16 inch diameters of flexible fiberglass wool duct as well as un-insulated flexible duct. The strong, but lightweight, 100% recycled polymer support will not weigh down ducting. UL Classified 2043 and GreenSpec Listed.



FDS1



| Catalog Number | Description | Nominal Dimensions in. (cm) | Net Wt. oz. (g) | Duct Diameter | Tie Requirements |
|----------------|-----------------------|--|--------------------|---|--|
| FDS1 | Flexible Duct Support | 15 x 11-1/4 x 3 (38.1 x 28.6 x 7.6) | 3 (85) | 4-10 in. (10.2-25.4 cm) 12-14 in. (30.5-35.6 cm) 16 in. (40.6 cm) | 2) 36 in. (91.4 cm) 2) 48 in. (121.9 cm) 4) 36 in. (91.4 cm) |