




FEATURES

With their smooth, flat and edgeless design, Oscar family recessed luminaires become a seamless part of ceiling decor. With 3 different light modules suited for ambient and accent lighting, the Oscar family is as highly functional as it is visually appealing. Numerous ordering options allow for further functional and artistic customization. Oscar recessed luminaires are available in larger sizes with higher lumen packages making them ideal for both residential and commercial settings.




SPECIFICATIONS

FIXTURE BODY	18 gauge powder coated steel body. Aluminum powder coated trim or trimless mesh plate
INSTALLATION TYPE	Remodel/existing ceiling N/C plate, IC Box on page 2
CUT HOLE	Trim: Ø3 1/8" Trimless: Ø3 1/4" Trimless Wood Ceiling Please contact us for detail
COLOR FINISH	Black/White/Custom
LIGHT MODULE	High output, high efficiency LED COB. Lumen Maintenance: 70% @ 50,000 hrs
INPUT VOLTAGE	120V - 277V
WATTAGE	10W IC Rated, 15W Non-IC Rated
POWER SUPPLY	ERP 10W or 15W, Constant Current 250mA or 350mA power supply Minimum operating temperature: -30° Enclosed in a Junction box with 12" flexible cable to mate to module connector
CRI	90+
DIMMING	TRIAC/ELV/0-10V
DELIVERED LUMENS	10W IC: 810 LM, 10H IC: 1060 LM, 15W Non-IC: 1430 LM, Dim to Warm: 15W, 785 LM
CCT OPTIONS	2700K/3000K/3500K/4000K, DTW (Dim to warm)
REFLECTORS	(N) Narrow 15°/(M) Medium 24°/(W) Wide 38°/(F) Wide Flood 50°
DIFFUSERS	(CL) Clear/(LN) Linear Spread/(HC) Honeycomb (FR) Frosted/(SP) Solite
APPROVAL	Wet
ELECTRICAL APPROVAL	Compliant
WARRANTY	


SPECIFICATION GUIDE

OSCAR	3	SHAPE		TRIM/ TRIMLESS		FINISHES		LIGHT MODULE		BAFFLE FINISHES		WATTAGE		CCT	BEAM ANGLE		DIFFUSER		ADD-ONS		
OSC	3	R	ROUND	T	TRIM	01	BLACK	RF	RECESSED FIXED	01	MATTE BLACK	10	10W	27	N	15°	CL	CLEAR	EM	EMERGENCY MICRO INVERTER*	
				TL	TRIMLESS	02	WHITE			02	MATTE WHITE	10 H	High Lumen 10W	30	M	24°	LN	LINEAR SPREAD			
				WC	TRIMLESS WOOD CEILING					03	GOLD	15	15W	35	W	38°	HC	HONEYCOMB			
										04	CHROME			40	F	50°	FR	FROSTED			
										05	DARK CHROME							SP			SOLITE
										06	HAZE										
ORDERING GUIDE EXAMPLE: Oscar / 3 / Round / Trim / White / Recessed Fixed / Chrome / 15W / 2700K / 15° Beam Angle / Clear Diffuser CODE: OSC-3-R-T-02-RF-04-15-27-N-CL										Dim To Warm 15W only											
* Part# 47184-015 Sold Seperate, see page 2 for details.																					

REFLECTOR OPTIONS



DIFFUSER OPTIONS



BAFFLE FINISHES



ADD-ONS



SINUSOIDAL EMERGENCY MICRO INVERTER

- Remote Mounted
- 150W Max 0-10V
- 25W Max Triac/elv.
- Can accommodate multiple fixtures
- Recommended to load to 80%
- 90 Min Service
- See Spc Sheet for more details

NEW CONSTRUCTION PLATE + IC BOXEX + SMASH PLATE



NEW CONSTRUCTION PLATE

TRIM

43784-011

TRIMLESS

30534-018

CUT HOLE:

Trim: Ø3 1/8"

Trimless: Ø3 1/4"





SMASH PLATE

TRIM

48005-012

TRIMLESS

47876-019



CUT HOLE:

Trim: Ø3 1/8"

Trimless: Ø3 1/4"



TRIM

AT/IC Box: 46746-016

CUT HOLE:

Trim: Ø3 1/8"

Trimless: Ø3 1/4"


TRIMLESS

AT/IC Box: 46739-018

CUT HOLE:


Trim: Ø3 1/8"


Trimless: Ø3 1/4"




DRIVERS

- Compatible with TRIAC (forward-phase or leading-edge) ELV (reverse-phase or trailing edge) and 0-10V dimmers.
- ESSxxxW models: TRIAC and ELV dimming only at 120 Vac
- ESSxxxW models: ELV dimming only at 230 Vac
- 90° C maximum case hot spot temperature
- Class 2 power supply
- Lifetime: 50,000 hours at 70° case hot spot temperature (some models have a higher lifetime)
- IP64-rated (IP66 for ESST) case with silicone-based potting
- Protections: Output open load, over-current and short-circuit (hiccup), and over-temperature with auto recovery.
- Conducted and radiated EMI: Compliant with FCC CFR Title 47 Part 15 Class B (120 Vac) and Class A (277 Vac), and EN55015 (CISPR 15) at 220, 230, and 240 Vac.
- Complies with ENERGY STAR®, DLC (DesignLight Consortium®) and CA Title 24 technical requirements
- Worldwide safety approvals







10W 1-LIGHT FIXED NARROW CLEAR




15W 1-LIGHT FIXED NARROW CLEAR




10W 1-LIGHT FIXED MEDIUM CLEAR




15W 1-LIGHT FIXED MEDIUM CLEAR




10W 1-LIGHT FIXED WIDE CLEAR




15W 1-LIGHT FIXED WIDE CLEAR




10W 1-LIGHT FIXED NARROW CLEAR




15W 1-LIGHT FIXED NARROW CLEAR




10W 1-LIGHT FIXED MEDIUM CLEAR



15W 1-LIGHT FIXED MEDIUM CLEAR



10W 1-LIGHT FIXED WIDE CLEAR



15W 1-LIGHT FIXED WIDE CLEAR

